



SPECIFICATIONS

ACTUATION POWER:
0.5 HP [0.37kW]

HOLDING FORCE:
3000 LB [13.3kN]

FLOW CONTROL:
INTERNAL THRUSTER
ADJUSTABLE,
ALLOWING SOFT
APPLICATION OF
TRIPPER CLAMP

MOUNTING:
SILL BEAM

OPERATION:
SPRING APPLIED,
ELECTRICALLY
RELEASED
- MANUAL HAND
RELEASE ALSO

LIMIT SWITCH:
6A@120VAC
VA RATINGS:
MAKE=7200VA
BREAK=720VA
IEC947-5-1
EN60947-5-1

WEIGHT TOTAL:
145 KG [320 LB]

NOTE:
THESE DIMENSIONS
ARE FOR ESTIMATING
PURPOSED ONLY



TRB-A30-EB150/60 RAIL CLAMP
SPRING SET / THRUSTER RELEASE

UOS TOLERANCES +/- CASTINGS 1/32" CUT PLATE 1/32" MACHINING .005" LOCATION .015"	BY: DJ	DATE: 020729	REV: .4 030327
	SCALE:		REV:
	REF: B4368-21.0		DWG. NO.
	PATH: stb/ric/trp/trbt30001b		BTRBT-1.5